

BRAKE

SERVICE DATA

SS0AA-02

Brake pedal height (from asphalt sheet)		138.5 – 148.5 mm (5.453 – 5.846 in.)
Brake pedal freeplay		1 – 6 mm (0.04 – 0.24 in.)
Brake pedal reserve distance at 490 N (50 kgf, 110.2 lbf)	w/o ABS	More than 60 mm (2.36 in.)
Brake pedal reserve distance at 490 N (50 kgf, 110.2 lbf)	w/ ABS	More than 55 mm (2.17 in.)
Brake booster push rod to piston clearance (w/ SST)		0 mm (0 in.)
Front brake pad thickness	STD	10.0 mm (0.394 in.)
Front brake pad thickness	Minimum	1.0 mm (0.039 in.)
Front brake disk thickness	STD	18.0 mm (0.709 in.)
Front brake disk thickness	Minimum	16.0 mm (0.630 in.)
Front brake disk runout	Maximum	0.05 mm (0.0020 in.)
Rear brake drum inside diameter	STD	180.0 mm (7.087 in.)
Rear brake drum inside diameter	Maximum	181.0 mm (7.126 in.)
Rear brake shoe lining thickness	STD	4.0 mm (0.157 in.)
Rear brake shoe lining thickness	Minimum	1.0 mm (0.039 in.)
Rear brake drum to shoe clearance		0.6 mm (0.024 in.)
Parking brake lever travel at 196 N (20 kgf, 44.1 lbf)		5 – 8 clicks