

STARTING

SERVICE DATA

SS0MY-12

Starter (Planetary type)	Rated voltage and output power		12 V 0.8 kW
	No-load characteristics	Current	90 A or less at 11.5 V
		rpm	3,000 rpm or more
	Center bearing oil clearance	STD	0.01 – 0.06 mm (0.0004 – 0.0024 in.)
		Maximum	0.2 mm (0.0078 in.)
	Brush length	STD	14.0 mm (0.551 in.)
		Minimum	0.9 mm (0.0354 in.)
	Spring installed load	STD	13.7 – 17.6 N (1.4 – 1.8 kgf, 3.1 – 4.0 lbf)
		Minimum	8.8 N (0.9 kgf, 2.0 lbf)
	Commutator		
Starter (Reduction type)	Diameter	STD	28.0 mm (1.102 in.)
		Minimum	27.0 mm (1.063 in.)
	Undercut depth	STD	0.6 mm (0.024 in.)
		Minimum	0.2 mm (0.008 in.)
	Circle runout	Maximum	0.05 mm (0.0020 in.)
	Rated voltage and output power		12 V 1.0 kW
	No-load characteristics	Current	90 A or less at 11.5 V
		rpm	3,000 rpm or more
	Brush length	STD	13.5 mm (0.531 in.)
		Minimum	8.5 mm (0.335 in.)
	Spring installed load	STD	17.6 – 23.5 N (1.79 – 2.41 kgf, 3.9 – 5.3 lbf)
		Minimum	11.8 N (1.2 kgf, 2.6 lbf)
	Commutator		
	Diameter	STD	30.0mm (1.181 in.)
		Minimum	29.0 mm (1.142 in.)
	Undercut depth	STD	0.6 mm (0.024 in.)
		Minimum	0.2 mm (0.008 in.)
	Circle runout	Maximum	0.05 mm (0.0020 in.)
	Magnetic switch		
	Contact plate for wear	Maximum	0.9 mm (0.035 in.)